



??????? :: ??????
 ??? ?????? :: ARGO CAI200
 ??? ???? :: 10
 ?????: 0.55kg
 ??????50.00mm x 74.00mm x 186.00mm

?????: 0.00EGP

????? ???????

Access Control	
Ingress Protection	IP65
Card	ARGO CAI: HID iClass Card Support (Read/Write) HID Prox, EM Prox, Desfire EV1 & EV2 (CSN Read) and Mifare Classic (CSN Read)
Max. Users	50,000
Event Buffer	500,000
Wi-Fi	Yes (802.11 b/g/n)
Bluetooth®	Yes (8m Range)
Ethernet	Yes (10/100 Mbps – 1 port)
PoE	Yes (IEEE 802.3 af)
Wiegand	Yes (Selectable IN/OUT) IN: 26 Bit format OUT: Configurable
Exit Switch Port	Yes
Door Lock Relay	Yes (30VDC @ 2A, Dry Contacts NO/NC/COM)
Door Lock Power	Internal PoE Power: 12VDC @ 0.250 A Internal Adapter Power 12VDC @ 0.5 A External Power 12VDC @ 2A
Aux-In	NO
Aux-Out	NO
Reader Interface Types	Interface RS232 WiegandPower 12VDC @ 0.5ALED and Buzzer Control Allowed – GREEN LED Buzzer
CPU	800 MHz ARM cortex A8 based processor
Memory	512 MB DDR3 RAM + 512 MB Flash Memory
Buzzer	Yes

Operating Temperature	0°C to 50°C
Humidity	5% to 95 % RH Non-Condensing
Tamper Detection	Yes
Wall Mount	Yes
Power Adapter	12VDC @ 2A (CE, FCC, BIS)
Battery Backup	No
????	Yes
?????? - ??????	Yes
???	3.5" IPS LCD (Touch Screen)
??? ?????	480 x 320 Pixel
???? ?????????	Yes (Gorilla Glass 3)
????? ?????????	IK06
???? ?????? ???????	-20°C to 60°C
3G/4G/LTE	Yes (Additional USB Modem)
USB	Yes (USB 2.0) Micro USB-Type B
???????? ???????	Yes

????? ?????????

