



??????? :: ??????
 ??? ?????? :: VEGA FAM
 ??? ???? :: 10
 ?????: 0.54kg
 ??????38.00cm x 91.00cm x 186.00cm

?????: 0.00EGP

????? ???????

Access Control	
Credential Support	Bluetooth® (BLE), Fingerprint, RFID Card, PIN
Ingress Protection	IP65
Card	MIFARE Classic®, DESFire EV1 and EV2(Read/Write), NFC Tag
Max. Users	50,000
Event Buffer	500,000
Wi-Fi	Yes
Bluetooth®	Yes
Ethernet	Yes (10/100 Mbps)
PoE	Yes (IEEE 802.11 b/g/n)
RS-232	Yes
Wiegand	Yes (Selectable IN/OUT) IN: 26 Bit format OUT: Configurable
Exit Switch Port	Yes
Door Status Sense	Programmable NO, NC, Supervised
Door Lock Relay	30V DC @ 1A, Form C, DPDT Relay
Door Lock Power	12V DC @ 0.5A (Power to external Lock from Device) 30V DC @2 A (Power to lock from External power source)
Aux-In	Yes
Aux-Out	Yes
Reader Interface Types	RS-232 and Wiegand
CPU	800 MHz ARM Cortex A8 based Processor
Memory	256 MB Flash + 512 MB DDR3 RAM
Buzzer	Yes

Operating Temperature	0°C to +50°C (32°F to 122°F)
Humidity	5% to 95% RH Non-Condensing
Tamper Detection	Yes
Power	12V DC @ 2A
Power to Door Lock	12V DC @ 0.5A (Power to Lock from Device)
System Integration	API for Software Integration
Operational Modes	Direct Door with COSEC CENTRA / COSEC VYOM Panel Door with COSEC PANEL200P”
Wall Mount	Yes
Power Adapter	12VDC @ 2A (CE, FCC, UL, BIS)
Battery Backup	Yes
???	3.5? TFT Display with Capacitive Touch Panel
??? ?????	320 x 240 Pixel
USB	1 USB Port (Data Transfer and 3G/4G/LTE Dongle)

????? ?????????

