



??????? :: ??????  
 ??? ?????? :: VEGA CAI  
 ???? ???????? :: 10  
 ?????: 0.54kg  
 ??????38.00mm x 91.00mm x 186.00mm

**?????: 0.00EGP**

????? ????????

| Access Control         |                                                                                                                              |
|------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Credential Support     | Bluetooth® (BLE), RFID Card, PIN                                                                                             |
| Ingress Protection     | IP65                                                                                                                         |
| Card                   | HID iClass Card Support (Read/Write), HID Prox, EM Prox, Desfire EV1 & EV2 (CSN Read) and Mifare Classic (CSN Read), NFC Tag |
| Max. Users             | 50,000                                                                                                                       |
| Event Buffer           | 500,000                                                                                                                      |
| Wi-Fi                  | Yes                                                                                                                          |
| Bluetooth®             | Yes                                                                                                                          |
| Ethernet               | Yes (10/100 Mbps)                                                                                                            |
| PoE                    | Yes (IEEE 802.11 b/g/n)                                                                                                      |
| RS-232                 | Yes                                                                                                                          |
| Wiegand                | Yes (Selectable IN/OUT) IN: 26 Bit format OUT: Configurable                                                                  |
| Exit Switch Port       | Yes                                                                                                                          |
| Door Status Sense      | Programmable NO, NC, Supervised                                                                                              |
| Door Lock Relay        | 30V DC @ 1A, Form C, DPDT Relay                                                                                              |
| Door Lock Power        | 12V DC @ 0.5A (Power to external Lock from Device) 30V DC @2 A (Power to lock from External power source)                    |
| Aux-In                 | Yes                                                                                                                          |
| Aux-Out                | Yes                                                                                                                          |
| Reader Interface Types | RS-232 and Wiegand                                                                                                           |
| CPU                    | 800 MHz ARM Cortex A8 based Processor                                                                                        |
| Memory                 | 256 MB Flash + 512 MB DDR3 RAM                                                                                               |

|                       |                                                                               |
|-----------------------|-------------------------------------------------------------------------------|
| Buzzer                | Yes                                                                           |
| Operating Temperature | 0°C to +50°C (32°F to 122°F)                                                  |
| Tamper Detection      | Yes                                                                           |
| Power                 | 12V DC @ 2A                                                                   |
| Power to Door Lock    | 12V DC @ 0.5A (Power to Lock from Device)                                     |
| System Integration    | API for Software Integration                                                  |
| Operational Modes     | Direct Door with COSEC CENTRA / COSEC<br>VYOM Panel Door with COSEC PANEL200P |
| Operational Modes     | 5% to 95% RH Non-Condensing                                                   |
| Wall Mount            | Yes                                                                           |
| Power Adapter         | 12VDC @ 2A (CE, FCC, UL, BIS)                                                 |
| Battery Backup        | Yes                                                                           |
| ???                   | 3.5" TFT Display with Capacitive Touch Panel                                  |
| ??? ?????             | 320 x 240 Pixel                                                               |
| USB                   | 1 USB Port (Data Transfer and 3G/4G/LTE<br>Dongle)                            |

????? ?????????

