



??????? :: ??????
 ??? ?????? :: VEGA FAXQ
 ??? ???? :: 10
 ?????: 0.54kg
 ??????38.00mm x 91.00mm x 186.00mm

?????: **0.00EGP**

????? ???????

Access Control	
Credential Support	Fingerprint, RFID Card and PIN
Max. Users	50,000
Event Buffer	500,000
Wi-Fi	Yes (802.11 b/g/n)
Ethernet	Yes (10/100 Mbps on Ethernet)
PoE	Yes (IEEE 802.3 af)
Exit Switch Port	Yes
Door Status Sense	Programmable NO, NC, Supervised
Door Lock Relay	Form C, SPDT Relay (Max 2A@30 VDC)
Door Lock Power	Internal 12VDC @ 0.5A or External
Aux-In	Programmable NO, NC, Supervised
Aux-Out	Form C, SPDT Relay (Max 2A@30 VDC)
Reader Interface Types	RS 232, and Wiegand IN/OUT
CPU	800 MHz ARM Cortex A8 based Processor
Memory	256 MB Flash + 512 MB DDR3 RAM
Buzzer	Yes
Operating Temperature	0°C to + 50°C (32°F to 122°F)
Humidity	5% to 85% RH Non-Condensing
Tamper Detection	Yes
Power	12 VDC @ 2A
System Integration	Software API for Software Integration
Operational Modes	Direct Door with COSEC CENTRA Server Panel Door with COSEC PANEL LITE V2
Battery Backup	No Internal Battery Backup, External Through PSBB

???	3.5" TFT Display with Capacitive Touch Panel
USB	2 USB Ports (1 for Data Transfer and 1 for 2G-3G Dongle)

????? ????????

