



??????? :: ??????
??? ?????? :: ARC DC200P
???? ???????? :: 10
?????: 0.23kg
??????? 140.00mm x 24.00mm x 80.00mm

?????: **0.00EGP**

????? ????????

Access Control	
Max. Users	50,000
Wi-Fi	YES (IEEE 802.11 b/g/n)
Bluetooth®	YES (Configurable range: 1m – 8m)
Ethernet	YES (10/100 Mbps)
PoE	YES (IEEE 802.3 af/at)(PoE/PoE+) PoE: Up to 15.4 W PoE+: Up to 25.5 W
RS-485	YES
Wiegand	YES (Selectable IN/OUT) IN – 26 Bit format OUT – Configurable
Exit Switch Port	YES (2 Exit switch for connecting individually with Reader 1 & Reader 2)
Door Status Sense	YES (4 State – Programmable NO, NC and Supervised)
Door Lock Relay	YES (30V DC @2A, Dry Contacts NO/NC/COM)
Aux-In	YES (4-State)
Aux-Out	YES (Max. 30V DC @ 2A)
CPU	Cortex A8 800 MHz
Memory	256 MB Flash Memory + 256 MB (DDR3 SDRAM @800MHz) RAM memory
LED	1 Tri color LED
Operating Temperature	-10°C to +50°C (14°F to 122°F)
Humidity	5% to 95 % RH Non-Condensing
Power	Adaptor = 12V DC @ 2 A PoE+ = 12V DC @1.8 A
Power to Door Lock	With PoE: 12V DC@ 0.5A for 1 Lock With PoE+

	: 12V DC @ 1A For 1 lock or 12V DC @ 0.5A for 2 Lock (0.5A EACH LOCK) Adapter : 12V DC@ 0.5A at 1 Lock
System Integration	API for Software integration
Operational Modes	Direct/Panel door with COSEC CENTRA/ VYOM Panel door with Standalone COSEC PANEL200

????? ????????

