

TS-832PX



??????? :: ??? ?? ??? ??

??? ?????? :: TS-832PX

???? ???????? :: 10

?????: 7.05kg

???????180.20mm x 329.30mm x 280.80mm

?????: 60,000.00EGP

????? ????????

????? ????????????	AnnapurnaLabs Alpine AL324 ARM® Cortex-A57 4-core 1.7GHz processor
????? ???? ????? ???????????	64-bit ARM
????? ????????	?
???????	4 GB SODIMM DDR4(1 x 4 GB)
??? ?????? ??????????	8
??? ?????????? ??????????	3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
????? ???? ?????????? ???????	? (Not supported M.2 SSD)
???? USB ?????? 3.2	3
????? ???????	System fan: 2 x 120mm, 12VDC CPU fan: 1 x 60mm
????? ?????? ???????/???????	250W, 100-240V AC, 50/60Hz, 3.5A
Total Memory Slots	1 x SODIMM DDR4
Maximum Memory Capacity	16 GB (1 x 16 GB)
M.2 Drive Slots	Optional via a PCIe adapter
PCIe Expansion	1 Slot 1: PCIe Gen 2 x2 PCIe bandwidth limitations will restrict the NAS 10GbE

	performance. Card dimensions for PCIe slot?210 x 68.9x 24.76 mm / 8.27 x 2.71 x 0.97 inches.
Form Factor (RU)	Tower
Floating Point Unit	?
Flash Memory	512 MB (Dual boot OS protection)
SSD Cache Acceleration Support	?
Wake on LAN (WOL)	? Only the 2.5GbE port
Jumbo Frame	?
LED Indicators	System Status, LAN, USB, HDD1~8
Buttons	Power, Reset, USB Copy
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Consumption: Disk Standby Mode	27.949
System Warning	Voice prompts or Buzzer
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	700
Kensington Security Slot	?

????? ????????



