



????????? :: ??? ?? ??? ??
??? ?????? :: TS-433
??? ??????? :: 10
?????: 2.07kg
???????: 165.00mm x 160.20mm x 220.50mm
????? ??????:

????? ????????

????? ????????????	ARM 4-core Cortex-A55 2.0GHz processor
????? ???? ?????	64-bit ARM
???????????	
????? ????????	?
???????	4 GB on board (non-expandable) Note: Reserves some RAM for use as shared graphics memory.
?? ?????? ????????	4
?? ??????? ????????	3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
????? ???? ????????	?
?????	
???? USB ???? 3.2	1
????? ????????	1 x 120mm, 12VDC
????? ??????	Minimum 65W adapter (12VDC), 100-240VAC
??????/???????	
Maximum Memory Capacity	4 GB on board (non-expandable)
Form Factor (RU)	Tower
Graphic Processors	Mali-G52
Floating Point Unit	?
Hardware-accelerated Transcoding	?
Flash Memory	4 GB (Dual boot OS protection)
Wake on LAN (WOL)	?
Jumbo Frame	?

LED Indicators	System Status, LAN, USB, HDD1~4
Buttons	Power, Reset, USB Copy
Operating Temperature	0 - 40 °C (32°F - 104°F)
Storage Temperature	-20 - 70°C (-4°F - 158°F)
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
Power Consumption: Disk Standby Mode	8.45
System Warning	Buzzer
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	200
Kensington Security Slot	?

????? ????????



