



?????? :: ??? ?? ??? ??
??? ?????? :: TS-473A
???? ?????? :: 10
?????: 5.54kg
???????: 180.20mm x 199.30mm x 279.60mm
???? ?????:

????? ????????

10 Gigabit Ethernet Port	Optional via a PCIe adapter
2.5 Gigabit Ethernet Port (2.5G/1G/100M)	2(2.5G/1G/100M)
5 Gigabit Ethernet Port (5G/2.5G/1G/100M)	Optional via a PCIe adapter
Buttons	Power, Reset, USB Auto Copy
Drive Bay	4 x 3.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	3.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Encryption Engine	?? (AES-NI)
Fan	System fan: 1 x 120mm CPU fan: 1 x 60mm
Flash Memory	5GB (Dual boot OS protection)
Floating Point Unit	??
Form Factor	Tower
GPU pass-through	??
Graphic Processors	Optional via a PCIe adapter
Hardware-accelerated Transcoding	Optional via a PCIe adapter
HDMI™ Output	Optional via a PCIe adapter
Hot-swappable	??
Jumbo Frame	??
LED Indicators	Status/Power, USB, LAN, Drive 1-4, M.2 SSD 1-2
M.2 Slot	2 x M.2 2280 PCIe Gen3 x1 slots
Max. Number of Concurrent Connections	2000

(CIFS) - with Max. Memory	
Maximum Memory	64 GB (2 x 32 GB)
Memory Slot	2 x SODIMM DDR4 Support ECC memory
Operating Temperature	0 - 40 °C (32°F - 104°F)
PCIe Slot	2 Slot 1: PCIe Gen 3 x4 Slot 2: PCIe Gen 3 x4
Power Consumption: Disk Standby Mode	19.576
Power Consumption: Operating Mode, Typical	29.792 W
Power Supply Unit	250W, 100-240V AC, 50-60Hz, 3.5A
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
SSD Cache Acceleration Support	??
Storage Temperature	-20 - 70°C (-4°F - 158°F)
System Memory	8 GB SODIMM DDR4 (1 x 8 GB)
System Warning	Buzzer
USB 3.2 Gen 2 (10Gbps) Port	3 x Type-A USB 3.2 Gen 2 5V/1A 10Gbps 1 x Type-C USB 3.2 Gen 1 5V/1A 5Gbps
Wake on LAN (WOL)	??
????? ??????????	AMD Ryzen™ Embedded V1500B 4-core/8-thread 2.2 GHz processor
????? ????	64-bit x86
????? ????????	

????? ????????



