



?????? :: ??? ?? ??? ??
??? ?????? :: TS-832PX
???? ?????? :: 10
?????: 7.05kg
???????: 180.20mm x 329.30mm x 280.80mm
???? ?????:

????? ??????

10 Gigabit Ethernet Port	2 x 10GbE SFP+
2.5 Gigabit Ethernet Port (2.5G/1G/100M)	2 (2.5G/1G/100M/10M)
Buttons	Power, Reset, USB Copy
Drive Bay	8 x 3.5-inch SATA 6Gb/s, 3Gb/s
Drive Compatibility	3.5-inch bays: 3.5-inch SATA hard disk drives 2.5-inch SATA hard disk drives 2.5-inch SATA solid state drives
Encryption Engine	??
Fan	System fan: 2 x 120mm, 12VDC CPU fan: 1 x 60mm
Flash Memory	512 MB (Dual boot OS protection)
Floating Point Unit	??
Form Factor	Tower
Hot-swappable	?? (Not supported M.2 SSD)
Jumbo Frame	??
Kensington Security Slot	??
LED Indicators	System Status, LAN, USB, HDD1~8
M.2 Slot	Optional via a PCIe adapter
Max. Number of Concurrent Connections (CIFS) - with Max. Memory	700
Maximum Memory	16 GB (1 x 16 GB)
Memory Slot	1 x SODIMM DDR4

Operating Temperature	0 - 40 °C (32°F - 104°F)
PCIe Slot	1 Slot 1: PCIe Gen 2 x2 PCIe bandwidth limitations will restrict the NAS 10GbE performance. Card dimensions for PCIe slot?210 x 68.9x 24.76 mm / 8.27 x 2.71 x 0.97 inches.
Power Consumption: Disk Standby Mode	27.949
Power Consumption: Operating Mode, Typical	50.858 W Tested with drives fully populated.
Relative Humidity	5-95% RH non-condensing, wet bulb: 27°C (80.6°F)
SSD Cache Acceleration Support	??
Storage Temperature	-20 - 70°C (-4°F - 158°F)
System Memory	4 GB SODIMM DDR4(1 x 4 GB)
System Warning	Voice prompts or Buzzer
USB 3.2 Gen 1 port	3
Wake on LAN (WOL)	?? Only the 2.5GbE port
????? ??????????	AnnapurnaLabs Alpine AL324 ARM® Cortex-A57 4-core 1.7GHz processor
????? ????	64-bit ARM
?????????	
???? ?????	250W, 100-240V AC, 50/60Hz, 3.5A
?????/??????	



