

# SIMPO



**Brand:** Teletek  
**Product Code:** SIMPO  
**Availability:** 5  
**Weight:** 4.20kg  
**Dimensions:** 81.20mm x 306.00mm x 412.00mm  
**Call for Price:**

## Short Description

SIMPO is the perfect solution for smaller addressable installations.

## Description

SIMPO is the perfect solution for smaller addressable installations. The addressable panel supports up to two loops with coverage of 48 zones. 250 devices operating on Teletek Electronics communication protocol could be connected to each loop. System status is visualized via LCD display and LED indication. Up to 64 Simpo panels can be connected in RS485 redundant network or Ethernet network. Direct programming with ProsTE software is available. The panel comes in a metal casing with a multilingual LCD display and front foil for easier customization.

## Specification

Fire Alarm	
Back-up Power Supply	1 battery, 12V/ 18Ah
Devices per loop	250
Display	4*40 symbols LCD
Electrical output	4.2A
Frequency	47 ÷ 440 Hz
Inputs	3
Loops	2
Main Power Supply	90 ÷ 264 VAC
Memory LOG	10 / 240 events

Multi language support	Yes
Operating temperature	-5°C to +40°C
Outputs (monitored, relay type)	5
Outputs (non monitored, programmable, relay type)	4
Panels in RS485 redundant network (optional module)	Up to 64
Programming	ProsTE software
Standard	EN54 – 2/4
Thermal printer	Optional
Zones	48

## Product Gallery

