# RackStation RS1221+

Brand: Synology Product Code: RS1221+ Availability: 10 Weight: 6.90kg Dimensions: 88.00mm x 482.00mm x 306.60mm Call for Price:

#### **Short Description**

Synology 8 Bay RackStation RS1221+ (Diskless)

Description

# **Compact and reliable**

The RS1221RP+/RS1221+, at only 30 to 38 centimeters deep, is built for space-sensitive deployments. Boasting over 100K 4K random read IOPS and 2,315 MB/s sequential read<sup>1</sup>, the RS1221RP+/RS1221+ is equipped to handle heavy workloads in data-intensive environments. The RS1221RP+ additionally features an extra level of protection with redundant power supplies.



#### Compute

AMD Ryzen<sup>™</sup> V1500B quad-core 2.2 GHz

# ≁ | | |

# Throughput

2,300 MB/s seq. read 100K 4K random read IOPS<sup>1</sup>

200003

### Memory

4 GB ECC DDR4 Up to 32 GB



# Compact

30cm depth (38cm for RP model)

### A compact design for space efficiency

The RS1221+ and its RX418 expansion units are designed to help you save space in compact deployments. At only 30 centimeters, half the length of a typical 2U unit, it fits perfectly snug onto 2-post or shallow rackmount enclosures. The RS1221RP+ with dual power supplies comes in at 38 cm, also fitting most shallow depth enclosures.<sup>2</sup>

Fits into shallow rackmount enclosures

Easy-to-install on 2-post racks

# **Built for reliability**

#### **Redundant power**

Reduce the chance that power disruptions on a single distribution channel or PDU causes data and service availability degradation.

#### Maximize service availability

When paired with another identical unit, Synology High Availability enables automatic minute-level failover between two clustered servers in the event of a server failure to minimize service downtime

#### Data integrity and protection

ECC memory and the Btrfs file system bring higher reliability and snapshot capabilities

to help prevent data corruption and simplify data protection.

# High performance storage for anything

Up to 2,315/1,147 MB/s sequential read and write throughput and over 100K/54K random read/write IOPS ensures ample performance for demanding workloads.<sup>1</sup>

# With room to grow with you

Easily upgrade the RS1221RP+/RS1221+ to match your usage environment, whether it's for performance, faster networking, or higher storage capacity.<sup>3</sup>

#### **SSD** cache

Boost read/write IOPS over HDD-only arrays by 16X or more with NVMe or SATA SSD Cache<sup>4</sup>

**10GbE ready** 

**Storage expansion** 

Data protection solutions, built-in

### Maximize data availability

#### Hyper Backup

A comprehensive backup and recovery solution for added data protection. Create backup destinations locally, on another Synology device, rsync servers, or cloud-based destinations, such as Google Drive, Dropbox, S3-compatible destinations, and Synology C2 Storage, a dedicated backup destination for Synology devices. Deduplication, integrity checks, and incremental transfer technology reduce bandwidth and storage use.

### **Snapshot Replication**

Easily schedule flexible point-in-time backups of shared folders and LUNs with an RPO as low as 5 minutes and recovery in seconds. Set up replication and failover to other Synology storage systems for fast RTOs and minimal service disruption

### Protect your entire IT infrastructure

#### Protect your entire office with Active Backup

The Active Backup suite enables administrators to easily secure their entire IT infrastructure by backing up mission-critical data to their NAS, including Windows & Linux workstations and servers, file servers, VMware and Hyper-V virtual machines, and Microsoft 365 and Google Workspace accounts. Benefit from deduplication, multiversioning to quickly jump back in time, and additional data efficiency optimizations for reduced bandwidth and storage use

OSM Specifications		RS1221+
torage Management	Maximum Single Volume Size	108 TB
	Maximum Internal Volume	64
	Number	
	SSD Read/Write	
	Cache (Determining cache	
	size)	
	SSD TRIM	
	Supported RAID Type	Synology Hybrid
	Supported KAID Type	RAID
		Basic
		• JBOD
		• JBOD • RAID 0
		• RAID 0 • RAID 1
		• RAID 1 • RAID 5
		• RAID 6
		RAID 10
	RAID Migration	Basic to RAID 1
		Basic to RAID 5
		• RAID 1 to RAID 5
		RAID 5 to RAID 6
	Volume Expansion with	Synology Hybrid
	Larger HDDs	RAID
		• RAID 1
		• RAID 5
		• RAID 6
		• RAID 10
	Volume Expansion by	<ul> <li>Synology Hybrid</li> </ul>
	Adding a HDD	RAID
		• JBOD
		• RAID 5
		• RAID 6
	Global Hot Spare	<ul> <li>Synology Hybrid</li> </ul>
	Supported RAID Type	RAID
		• RAID 1
		• RAID 5
		• RAID 6
		• RAID 10
	Notes	

<u>File System</u>	Internal Drives	• Btrfs
		• ext4
	External Drives	• Btrfs
		• ext4
		• ext3
		• FAT
		• NTFS
		• HFS+
		• exFAT
	Notes	
File Services	File Protocol	• SMB
		• AFP
		• NFS
		• FTP
		• WebDAV
		• Rsync
	Maximum Concurrent	1,000
	SMB/AFP/FTP	
	Connections	
	Maximum Concurrent	2,000
	SMB/AFP/FTP	
	Connections (with RAM	
	expansion)	
	Windows Access Control	
	List (ACL) Integration	
	NFS Kerberos	
	Authentication	
	Notes	
Account & Shared Folder	Maximum Local User	2,048
	Accounts	
	Maximum Local Groups	256
	Maximum Shared Folder	512
	Maximum Shared Folder	16
	Sync Tasks	
<u>Hybrid Share</u>	Maximum Hybrid Share	10
	Folders	
Hyper Backup	Folder and Package	
	Backup	
	Entire System Backup	
	Notes	
<u>High Availability</u>	Synology High Availability	
Log Center		

	Syslog Events per Second	1,000
Virtualization	VMware ESXi 6.5 and	
	VAAI	
	Windows Server 2016	
	Windows Server 2019	
	Windows Server 2022	
	Citrix Ready	
	OpenStack	
General Specifications	Supported Protocols	SMB1 (CIFS), SMB2,
		SMB3, NFSv3, NFSv4,
		NFSv4.1, NFS Kerberized
		sessions, iSCSI, HTTP,
		HTTPs, FTP, SNMP, LDAP,
		CalDAV
	Supported Browsers	Chrome
		• Firefox
		• Edge
		• Safari
	Supported Language	English, Deutsch, Français,
		Italiano, Español, Dansk,
		Norsk, Svenska, Nederlands,
		??????, Polski, Magyar,
		Português do Brasil,
		Português Europeu, Türkçe,
		?eský, ??????, ???, ???,
		????, ????
	Notes	
Central Management Syster		
Synology Chat	**	
<u>synology end</u>	Suggested Users	150
	Notes	
Download Station		
	Maximum Concurrent	80
	Download Tasks	
SAN Manager		
<u>or at y artumuzor</u>	Maximum iSCSI Target	128
	Number	
	Maximum LUN	256
	LUN Clone/Snapshot,	
	Windows ODX	
	Notes	
	# 101C3	

MailPlus Server	Free Email Accounts	5 (Additional accounts
		require purchase of licenses)
	Suggested Users	750
	Notes	150
Madia Campon	notes	
<u>Media Server</u>		
	DLNA Compliance	
<u>Synology Photos</u>		
	Facial Recognition	
	<b>Object Recognition</b>	
Snapshot Replication		
	Maximum Snapshots per	1,024
	Shared Folder	
	Maximum of System	65,536
	Snapshots	03,550
Secure : 11 and a Station	Shapshots	
Surveillance Station		
	Default Licenses	2 (Additional cameras require
		purchase of licenses)
	Suggested Maximum IP	• 1080p: 40 channels,
	<b>Cameras and Total FPS</b>	1050 FPS
	(H.264)	• 3M: 40 channels, 600
		FPS
		• 5M: 40 channels, 440
		FPS
		• 4K: 32 channels, 320
		FPS
	Suggested Maximum IP	• 1080p: 40 channels,
	Cameras and Total FPS	1200 FPS
	(H.265)	• 3M: 40 channels,
		1120 FPS
		• 5M: 40 channels, 600
		FPS
		• 4K: 40 channels, 480
		FPS
	Notes	~~
Synology Drive		
bynology Dilve	<b>Recommended Number of</b>	550 (the number of
		X X
	<b>Concurrent Sync Clients</b>	connections that can be
		maintained when the
		recommended number of
		hosted files was reached)
	<b>Recommended Number of</b>	50,000,000 (applies to files
	Hosted Files	indexed or hosted

		by <u>Synology Drive</u> . For file
		access through other standard
		protocols, refer to the File
		Services section above)
	Notes	
Synology Office		
	Suggested Users	4,500
	Notes	
Virtual Machine Manager		
	<b>Recommended Virtual</b>	8 <u>(Learn more)</u>
	Machine Instances	
	<b>Recommended Virtual</b>	8 (including 1 Free License)
	DSM Number <u>(Licenses</u>	
	required)	
	Notes	
VPN Server		
	Maximum Connections	40

### Specification

NAS	
CPU Architecture	64-bit
CPU Core	4
CPU Frequency	2.2 GHz
CPU Model	AMD Ryzen V1500B
CPU Quantity	1
Drive Bays	8
Expansion Port	1
Form Factor (RU)	2U
Hardware Encryption	Yes
Engine	
Hot Swappable Drive	Yes
Maximum Memory	32 GB (16 GB x 2)
Capacity	
Memory	4 GB DDR4 ECC SODIMM
PCIe Expansion	1 x Gen3 x8 slot (x4 link)
Power Supply Unit /	250 watts
Adapter	
RJ-45 1GbE LAN Port	4
System Fan	80 mm x 80 mm x 2 pcs
Total Memory Slots	2
USB 3.2 Gen 1 Port	2
Product Gallery	

