

DiskStation DS723+



Brand: Synology

Product Code: DS723+

Availability: 10

Weight: 1.51kg

Dimensions: 223.00mm x 106.00mm x
166.00mm

Call for Price:

Short Description

Synology 2-Bay DiskStation DS723+ (Diskless)

Description

Take your data management to the next level

Versatile smart storage that helps you consolidate and store your growing digital data.



Stunningly compact

Powerful functionality in a tiny package, with room for 10GbE and dual NVMe drives.



Consolidate and share

Flexibly store and organize 40 TB of data, then share with anyone.



Keep your data safe

Hardware and software engineered to protect your data — trusted by millions.

Simply faster

DS723+ can handle more demanding application workloads and a greater number of concurrent users compared to prior-generation systems. Experience faster file indexing in Synology Drive, photo organization in Photos, and concurrent file transfers.¹

Synology Drive
24%
faster file indexing

Synology Photos
25%
faster photo indexing

Multiple file transfers
32%
faster random write

The performance you need

Reduce transfer times with the DS723+, designed to accelerate your workloads. Easily add faster networking and NVMe drives to further boost performance.

Up to 471/225 MB/s read/write

Up to 10GbE networking

2 x M.2 NVMe cache & storage pool

Versatile and flexible storage

Make the most of high-performance networking and file access without taking up unnecessary space. DS723+ comes equipped with 2 bays and can scale up to 7 bays with the DX517 expansion unit as your data needs grow.

2 bays 20TB



7 bays 100 TB

Store, share, and protect

Manage all your documents, photos, and other files, back up applications and devices, and protect your assets with professional video surveillance.



Private cloud storage



Multi-layered backup



Smart surveillance

Private cloud storage

Access files from all your devices and protect them with smart versioning. Manage, share, and sync your data across locations.

Consolidate data management

Collaborate across sites

A private cloud for all your devices

Effortlessly deploy your own personal cloud with Synology's private cloud solution. Simplify file access and consolidate your data management to benefit from easier file sharing and collaboration.

Professional photo management

Efficiently back up and organize photos and videos with management tools for novice and professional users alike. Automatically organize your content into albums and create secure share links to share files with family, friends, or clients.



Sync files and folders between sites

Site-to-site file syncing allows collaborators to sync individual files or folders between Synology devices, whether at home, another office, or across the world. Combine convenient access with 100% data ownership.

Share data with the power of the cloud

Reduce your on-site storage footprint and benefit from data center network speeds with hybrid cloud technology. Set up Hybrid Share Folders to efficiently store cold data in the cloud, while keeping frequently accessed files cached locally on your DS723+ and accessible at LAN speeds.



Multi-layered backup

Back up files, folders, physical devices, VMs, and SaaS applications with free solutions, and protect your NAS with built-in technologies.

Back up all your devices

Protect your Synology system

Centralize your backup and recovery solution

Consolidate and automate backup tasks for PCs, file servers, VMs, SaaS applications, and more with Active Backup Suite. Administer device backups remotely through a centralized portal and quickly restore specific files or entire devices to keep your business up and running. Take advantage of built-in remote backup solutions designed to protect your data with seamless 3-2-1 backup configurations.



Perform full Synology system backups

Protect all data, applications, and configurations on your Synology systems with comprehensive scheduled backups to local and remote servers, external drives, or cloud storage destinations including Synology C2 Storage.

Protect folders and LUNs with snapshots

Configure efficient point-in-time snapshots of shared folders and LUNs at intervals as short as 5 minutes. Allow users to easily restore previous versions of files unassisted, quickly recover VMs, and copy snapshots to another server to benefit from rapid storage failover.

Smart surveillance

Transform your Synology device into a full-featured video management system for a wide range of compatible IP cameras.

Monitor and protect your business

Back up your surveillance footage

Synology Surveillance Station

Protecting your business has never been easier with centralized video management, support for over 8,300 IP camera models, and remote monitoring and playback of footage. Synology's surveillance management system provides all the tools you need for live monitoring, alerts, investigation, management, and backup.



Software

DSM Specifications

[Storage Management](#)

Maximum Single Volume Size 108 TB

Maximum Internal Volume Number 64

M.2 SSD Storage Pool Support*

SSD Read/Write Cache
[\(Determining cache size\)](#)

SSD TRIM

Supported RAID Type

- Synology Hybrid

RAID Migration

Volume Expansion with Larger HDDs

Volume Expansion by Adding a HDD

Global Hot Spare Supported RAID Type

- RAID
- Basic
- JBOD
- RAID 0
- RAID 1
- RAID 5 (with Expansion Unit)
- RAID 6 (with Expansion Unit)
- RAID 10 (with Expansion Unit)
- Basic to RAID 1
- Basic to RAID 5 (with Expansion Unit)
- RAID 1 to RAID 5 (with Expansion Unit)
- RAID 5 to RAID 6 (with Expansion Unit)
- Synology Hybrid RAID
- RAID 1
- RAID 5 (with Expansion Unit)
- RAID 6 (with Expansion Unit)
- RAID 10 (with Expansion Unit)
- Synology Hybrid RAID
- JBOD (with Expansion Unit)
- RAID 5 (with Expansion Unit)
- RAID 6 (with Expansion Unit)
- Synology Hybrid RAID (with Expansion Unit)
- RAID 1 (with Expansion Unit)
- RAID 5 (with Expansion Unit)

Notes

- RAID 6 (with Expansion Unit)
- RAID 10 (with Expansion Unit)
- Creating M.2 storage pools requires the use of Synology-verified SSDs, which are rigorously tested under extreme temperature conditions. Thermal parameters for SSDs and NAS units are fine-tuned to ensure optimal management of thermal conditions under I/O-intensive environments. ([Learn more](#))
- Usable capacity for each volume will be lower than the maximum volume size and is dependent on the filesystem and the amount of system metadata stored.
- Actual maximum storage pool and volume sizes vary depending on drives used, the number of drive bays available, and the RAID configuration.
- Each internal volume (may consist of multiple drives) is expandable up to 108TB.
- Btrfs

[File Services](#)

External Drives

- ext4
- Btrfs
- ext4
- ext3
- FAT
- NTFS
- HFS+
- exFAT
- SMB
- AFP
- NFS
- FTP
- WebDAV
- Rsync

File Protocol

Maximum Concurrent SMB/AFP/FTP Connections 500

Maximum Concurrent SMB/AFP/FTP Connections (with RAM expansion) 2,000

Windows Access Control List (ACL) Integration

NFS Kerberos Authentication

Notes

- Regarding data concerning tests with RAM expansion, all memory slots are installed with the maximum capacity of supported RAM.
- The testing standard was based on the maximum number of concurrent connections supported by this model. During the testing, 25% of the connections were used to transfer files concurrently. The transfer process guaranteed that the connections were not

interrupted; the minimum transfer speed was not guaranteed.

[Account & Shared Folder](#)

Maximum Local User Accounts 2,048
Maximum Local Groups 256
Maximum Shared Folder 512
Maximum Shared Folder Sync Tasks 8

[Hybrid Share](#)

[Hyper Backup](#)

Hybrid Share Folder Number 10
Folder and Package Backup
Entire System Backup
Notes Full-system backup requires DSM 7.2 or later.

[High Availability](#)

[Log Center](#)

Virtualization

Synology High Availability
Syslog Events per Second 800
VMware ESXi 6.5 and VAAI
Windows Server 2022
Citrix Ready
OpenStack

[General Specifications](#)

Supported Protocols SMB1 (CIFS), SMB2, SMB3, NFSv3, NFSv4, NFSv4.1, NFS Kerberized sessions, iSCSI, HTTP, HTTPs, FTP, SNMP, LDAP, CalDAV

Supported Browsers

- Chrome
- Firefox
- Edge
- Safari

Supported Language English, Deutsch, Français, Italiano, Español, Dansk, Norsk, Svenska, Nederlands, ???????, Polski, Magyar, Português do Brasil, Português Europeu, Türkçe, ?eský, ???????, ???, ???, ?????, ?????

Notes For an updated list of supported browser versions, check the [DSM Technical](#)

Specifications.

Add-on Packages [view the complete package list](#)

[Central Management System](#)

[Synology Chat](#)

Suggested Users
Notes

100

- Measured with simulated users, each with an average record of 20,000 messages, emojis, or stickers. The required server response time is below ten seconds.
- Models with expandable memory are tested with their maximum supported memory.

Download Station

Maximum Concurrent
Download Tasks

80

[SAN Manager](#)

Maximum iSCSI Target
Number

128

Maximum LUN

256

LUN Clone/Snapshot,
Windows ODX

[Synology MailPlus /](#)

[MailPlus Server](#)

Free Email Accounts

5 ([Additional accounts
require purchase of licenses](#))

Suggested Users
Maximum Server
Performance
Notes

500

1,224,000 emails per day,
approx. 37GB

- Suggested users is derived from testing in an environment with 20% heavy users (each with 20,000 pre-populated emails and receiving 240 emails per day) and 80% light users (each receiving an average of 20 emails per day). [Learn more](#)
- Models with 2 bays

and dual M.2 drive slots were installed with two SSDs for SSD cache.

- Models with expandable memory are tested with their maximum supported memory.
- The performance of the mail system will slightly decrease in high-availability mode due to data synchronization between the two servers.
- Functions that were enabled in all of the tests above: anti-spam, anti-virus, DNSBL, greylist, content scan, full-text search (English only).

[Media Server](#)
[Synology Photos](#)

DLNA Compliance
Facial Recognition
Object Recognition
Notes

Object recognition requires an upgrade of memory capacity to a minimum of 4 GB.

[Snapshot Replication](#)

Maximum Snapshots per Shared Folder
Maximum of System Snapshots

1,024
65,536

[Surveillance Station](#)

Default Licenses

Suggested Maximum IP Cameras and Total FPS (H.264)

2 [\(Additional cameras require purchase of licenses\)](#)

- 720p: 40 channels, 1200 FPS
- 1080p: 40 channels, 800 FPS
- 3M: 35 channels, 350

Suggested Maximum IP
Cameras and Total FPS
(H.265)

Notes

- FPS
- 5M: 28 channels, 280 FPS
- 4K: 17 channels, 170 FPS
- 720p: 40 channels, 1200 FPS
- 1080p: 40 channels, 1200 FPS
- 3M: 40 channels, 600 FPS
- 5M: 40 channels, 480 FPS
- 4K: 20 channels, 200 FPS
- Performance figures are obtained from testing conducted with the device fully populated with drives, with their default memory configuration, and under a continuous recording setup. Actual system capabilities may vary based on configuration, drive performance, enabled features, and the presence of additional workloads.
- Use [NVR Selector](#) to quickly find a suitable model based on your requirements.
- The maximum number of camera stream outputs is 2 times the suggested maximum number of

[Synology Drive](#)

Recommended Number of Concurrent Sync Clients	350 (the number of connections that can be maintained when the recommended number of hosted files was reached)	IP cameras.
Recommended Number of Hosted Files	5,000,000 (applies to files indexed or hosted by Synology Drive . For file access through other standard protocols, refer to the File Services section above)	
Notes		<ul style="list-style-type: none">• Exceeding the recommended numbers above will not block application operations, but may result in longer response time.• Utilizing SSD cache can significantly improve performance.• Models with expandable memory are tested with their maximum supported memory.• Btrfs file system and non-encrypted shared folders were used during the aforementioned testing.

[Synology Office](#)

Suggested Users	3,000	
Notes		<ul style="list-style-type: none">• Suggested users is derived from testing in an environment with 60% idle users (each logging in and viewing documents) and 40% active users (each executing

random actions at intervals of 20 to 40 seconds) operating within documents, each document having 30 users. [Learn more](#)

- Models with expandable memory are tested with their maximum supported memory.
- Client performance may affect maximum simultaneous editing users. Client PCs used for testing: Intel Core i3-3220 / 8GB RAM

Virtual Machine Manager	Recommended Virtual Machine Instances	4 (Learn more)
	Recommended Virtual DSM Number (Licenses required)	4 (including 1 Free License)
	Notes	The specifications vary depending on system configuration and memory size.
VPN Server	Maximum Connections	40

Specification

NAS	
Compatible Drive Type	3.5
Compatible Drive Type	3.5
CPU Architecture	64-bit
CPU Core	2
CPU Frequency	2.6 (base) / 3.1 (turbo) GHz
CPU Model	AMD Ryzen R1600
CPU Quantity	1
Drive Bays	2
Expansion Port	1
Hardware Encryption Engine	YES
Hot Swappable Drive	YES
M.2 Drive Slots	2 (NVMe)

Maximum Memory Capacity	32 GB (16 GB x 2)
Memory	2 GB DDR4 ECC SODIMM
PCIe Expansion	1 x Gen3 x2 network upgrade slot
Power Supply Unit / Adapter	65 watts 100V to 240V AC 50/60 Hz, Single Phase
RJ-45 1GbE LAN Port	2
System Fan	92 mm x 92 mm x 1 pcs
Total Memory Slots	2
USB 3.2 Gen 1 Port	1

Product Gallery

